











	10KV/15KV High Voltage Reed Relay			High Insulation Reed Relay			
产品外观 Appearance							
产品系列 Misensor Series No.	-04 series	-06 series	-150 series	HRX			
产品尺寸 Size(L×W× H)(mm)	68×19×19			54×17×17			
产品特性 Feature	<ul style="list-style-type: none"> • High Dielectric Strength Up to 15kV • Hermetically sealed for long life • Low Contact Resistance • Excellent Lifetime Characteristics • Custom Design Available For Coil Resistance And Pin Out. 						
■ Contact Rating							
触点形式 Contact Form	1 Form A						
线圈规格 Coil Rating Voltage	05V,12V,24V						
触点功率 Contact Rating	50W						
触点电流 Contact Current	3.0A						
触点载流 Carry Current	5.0A						
切换电压 Switching Voltage	7000V/10000V						
击穿电压 Breakdown Voltage	10000V/15000V						
■ Relay Specifications							
接触电阻 Contact Resistance	150mohm						
绝缘电阻 Insulation Resistance	1.0×10 ¹² ohm			1.0×10 ¹³ ohm			
机械寿命 Mechanical Life							
电气寿命 Electrical Life							
动作时间 Opreate Time	3.0ms						
释放时间 Release Time	1.5ms						
原理图 Layout(Top View)	Form A 	Form B 	Form A 	Form B 	Form A 	Form B 	Form A 