







	4000V High Voltage Reed Relay					6000V HV Reed Relay
产品外观 Appearance						
产品系列 Misensor Series No.	1 Form A	2 Form A	1 Form B	SIP-HV	1A+1B	2A06
产品尺寸 Size(L×W×H)(mm)	30.3×11.3×10	30.9×13.4×10	30.9×13.4×10	24.1×6.2×8.1	33×15.3×10	30.9×13.4×10
产品特性 Feature	<ul style="list-style-type: none"> • High Dielectric Strength Up to 4kV or 6kV • Hermetically sealed for long life • Low Contact Resistance • Excellent Lifetime Characteristics • Custom Design Available. 					
■ Contact Rating						
触点形式 Contact Form	1 Form A	2 Form A	1 Form B	1 Form A	Form 1A+1B	2 Form A
线圈规格 Coil Rating Voltage	5V,12V,24V					
触点功率 Contact Rating	100W					
触点电流 Contact Current	1.0A					
触点载流 Carry Current	2.5A					
切换电压 Switching Voltage	1000VDC					
击穿电压 Breakdown Voltage	4000V					6000V
■ Relay Specifications						
接触电阻 Contact Resistance	150ohm					
绝缘电阻 Insulation Resistance	1.0×10 ¹² ohm					
机械寿命 Mechanical Life						
电气寿命 Electrical Life						
动作时间 Opreate Time	1.0ms					
释放时间 Release Time	0.1ms					
原理图 Layout(Top View)	