

High Voltage Reed Relay Module				
产品外观 Appearance				
产品系列 Misensor Series No.	HRM 6A06	HRM 12A04	HRM 2A20	HRM 2A15
产品尺寸 Size(L×W×H)(mm)	169×107	169×107	100×80	107×76
产品特性 Feature	• 6 Channel High Voltage Switching Reed Relay Module	• 12 Channel High Voltage Switching Reed Relay Module	• 20 KVDC Reed Relay Module	• 2 Channel High Voltage Switching Relay Module
■ Contact Rating				
触点形式 Contact Form	Form 2A		Form 1A	
线圈规格 Coil Rating Voltage	5V,12V,24V	5V,12V,24V	12V,24V	12V,24V
触点功率 Contact Rating	100W	100W	50W	50W
触点电流 Contact Current	1.0A	1.0A	3.0A	3.0A
触点载流 Carry Current	2.5A	2.5A	5.0A	5.0A
切换电压 Switching Voltage	1000VDC	100VDC	7000/10000VDC	7000/10000VDC
击穿电压 Breakdown Voltage	6000V	4000V	20000V	10000/15000VDC
■ Relay Specifications				
接触电阻 Contact Resistance	300ohm	150ohm	300mohm	300mohm
绝缘电阻 Insulation Resistance	1.0×10 ¹² ohm	1.0×10 ¹² ohm	1.0×10 ¹² ohm	1.0×10 ¹² ohm
机械寿命 Mechanical Life				
电气寿命 Electrical Life				
动作时间 Opreate Time	1.0ms	1.0ms	3.0ms	3.0ms
释放时间 Release Time	0.1ms	0.1ms	1.5ms	1.5ms
原理图 Layout(Top View)				